












Model	Hindle	Cutting cros	ssection food thate	Chuite	kođpini	Overall diff	Het wei	Power Power
	in mm	in mm	in mm	in mm	in/mm	in/mm	Lbs Kgs	Нр
MO14	14 350	11.41x7.48 290x190	11x12 280x300	12.40 315	A 21.25/540 B 14.17/360 H 19.68/500	A 27.55/700 B 21.25/540 H 19.68/500	72.75 33	1/2

Cord & Plug: Attached 5.5 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-100 foot flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug fits a grounded receptacle and the flexible 3-wire cord with molded plug f















MO14 is a premium heavy-duty manual slicer with clear slice exit design: the entire area behind the blade is completely free. This slicer offers larger cut capacity, exact thickness regulation and smooth carriage stroke. Ideal machine for delicatessen, supermarkets and large size kitchens.

- Anodized aluminium casting construction: sturdy and light weight.
- 14" high quality hardened chromium steel alloy blade.
- Permanently attached knife ring guard.
- 1 to 1/16" slice thickness.
- Powerful and noiseless continuous use motor.
- Insulated switch. Overload protection manual reset.
- Multygrip belt drive: always the right grip.
- Carriage smooth glide motion also with heavy products.
- Slice thickness precision adjustment: gasket-sealed mechanism.
- Stainless steel food pusher toothed plate, removable for cleaning purposes.
- Equipped with SBR (Safe Blade Removal).
- Stainless steel ball-bearing blade pulley and special moisture-proof gasket.
- Built-in sharpener, removable for cleaning purposes.
- 30° carriage angle: good visibility of the slice exit area and better ergonomy.
- Non-slip rubber feet.

