



DXP912 Cabinet w/ DXP22128

DXP3373475

DXP3372404

RACK DOLLY

- Stainless dolly of 14 gauge stainless steel. Model No. DXP3372404
- Aluminum dolly of .125 aluminum Model No. DXP3111215
- 20-1/4"L x 20-1/4"W x 6"H
- All models are engineered to safely transport and store any load of 20" x 20" racks filled with cups and glasses.
- Four 4" swivel-type casters

TRAY CART

Model No. DXP3373470

- 16"L x 21"W x 31"H
- Stainless steel shelf and handle
- Four 4" swivel-type casters
- 31-1/2" high; 6-1/2" to top of shelf

RACK CART

Model No. DXP3373475

- 21"L x 21"W x 31"H
- Stainless steel shelf and handle
- Four 4" swivel-type casters
- 31-1/2" high; 6-1/2" to top of shelf

MODEL NUMBER

RACK DOLLY

- DXP3372404
- DXP3111215

TRAY CART

- DXP3373470

RACK CART

- DXP3373475

CABINET DOLLY

- DXP22128

CABINET DOLLY

Model No. DXP22128

- Aluminum dolly of .125 aluminum
- Four 4" swivel-type casters
- Dolly for 912 (Stackable Cabinet; Spec J-5)

OPTIONS

- DXPB - Corner bumper (Not available on DXP2-2128) (DXP337-3470 & DXP337-3475 receive two corner bumpers on side opposite handle and two rotating bumpers on handle side)
- DXPPB - Perimeter bumper (Available for DXP337-2404 & DXP311-1215 only)
- DXPWB - Two locking casters
- DXPY4 - Polyurethane 4" casters (set of 4)
- DXPY5 - Polyurethane 5" casters (set of 4)
- DXPCP - Correctional Package (Casters welded on unit)

MODEL#	DESCRIPTION	SHELF SIZE	HT. FROM FLOOR TO TOP OF HANDLE	GAUGE OF SHELVES	NO. OF SHELVES	SHELF HT. FROM FLOOR	OVERALL HEIGHT	LOAD CAP. (LBS)	SHIP WT.
DXP3373470	Stainless Steel Tray Cart (with Tubular handle)	21-1/2" X 16-1/2"	31"	18 ga. SS	1	10"	N/A	500	24
DXP3373475	Stainless Steel Rack Cart (with Tubular handle)	21-1/2" X 21-1/2"	31"	18 ga. SS	1	10"	N/A	500	24
DXP3372404	Stainless Steel Rack Dolly	20-1/2" Sq.	N/A	14 ga. SS	1	N/A	5 7/8"	500	14
DXP3111215	Aluminum Rack Dolly	20-1/2" x 21-1/2"	N/A	.125 Al	1	N/A	5 7/8"	500	14
DXP22128	Aluminum Cabinet Dolly	21-3/4"W X 28-3/8"D	N/A	.125 Al	1	N/A	7 3/4"	500	25

SPEC H-3

LIMITED WARRANTY: DINEX warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.

DINEX
www.dinex.com

4711 E. Hefner Road
Oklahoma City, OK 73131
800.654.8210
405.475.5600

We do not accept returns on any Dinex equipment or Dinex custom products. Please contact your local Dinex rep to ensure order accuracy prior to ordering.